



URL: https://www.foodequipment.com.au/media/catalog/product/b/m/bm11td-bain-marie.jpg

BM11TD Heated Wet 6 x ½ Pan Bain Marie Angled Countertop Display

Quick Overview

- Thermostat Contro
- Easy To Clean
- · Temp. Read-Out
- Drain Valves
- Air Insulated Tank With Double Skin Stainless Steel Construction In Satin Finish
- All Units Complete With Rear Sliding Doors On Rollers For Council Compliance
- In-Tank Temperature Probes For Accurate Measurement And Lower Running Costs
- Multiple Element Design For Reliable Operation And Even Temperature
- Improved Infra-Red Heat Lamp Configuration For Optimum Heat & Light
- Toughened Glass On All Sides For Maximum Safety
- · Rectangular Base To Easily Drop In To Bench Cut-Out
- Optimum Visibility Of Product No Unsightly Corner Post To Front
- Mechanical Thermostat Temperature Control
- Takes 6 x 1/2 Gastronorm Pans Up to 100mm Deep, Double row (Sold Separately)

* 15A plug required

Description

Heated Wet Six x 1/2 Pan Bain Marie Angled Countertop Display - BM11TD

All Stainless Steel

Heated: 35 to 85 $^{\circ}$ C

- Thermostat Contro
- · Easy To Clean
- · Temp. Read-Out
- Drain Valves
- Air Insulated Tank With Double Skin Stainless Steel Construction In Satin Finish
- All Units Complete With Rear Sliding Doors On Rollers For Council Compliance
- In-Tank Temperature Probes For Accurate Measurement And Lower Running Costs
- Multiple Element Design For Reliable Operation And Even Temperature
- Improved Infra-Red Heat Lamp Configuration For Optimum Heat & Light

1

- Toughened Glass On All Sides For Maximum Safety
- Rectangular Base To Easily Drop In To Bench Cut-Out
- Optimum Visibility Of Product No Unsightly Corner Post To Front
- Mechanical Thermostat Temperature Control
- Takes 6 x 1/2 Gastronorm Pans Up to 100mm Deep, Double row (Sold Separately)
- * Hot Food Holding Cabinets Only, Not Designed To Heat Product
- * 15A plug required
- 2 Years Parts and Labour + 2 Years Parts only Warranty with Product Registration

Your Shipping Specifications

Net Weight (Kg)	38
Width (mm)	1060
Depth (mm)	630
Height (mm)	700
Packing Width (mm)	720
Packing Depth (mm)	1120
Packing Height (mm)	730
Power	15A; 240V; 2.5kW