



FED-X S/S Two Door Upright Freezer - XURF600S1V

Quick Overview

- Stainless steel interior and exterior with rounded corners for easy cleaning
- Auto defrost
- Three levels of shelving plus base
- Self-closing lockable doors with heavy duty magnetic door seals
- HFCs and CFCs free foam body insulation
- Tropicalised for Australian conditions
- User friendly Digital controls and internal lighting
- Split door design for rapid recovery and energy saving
- Integrated door handle for easy cleaning
- Shelf and shelf support are designed to accommodate 2 x 1/1 GN pan
- Heavy duty evaporator and condenser fans
- Heavy duty castors with front wheel brakes
- 1/2 split door system can lower yearly running cost by up to 30%

Description

FED-X Stainless Steel Two Door Upright Freezer - XURF600S1V

- Net Capacity: 600L
- Cooling System: Fan forced cooling
- Temperature range: -18~-22°C
- Compressor: Cubigel
- Controller: Dixell
- Ambient Temperature: 43°C
- RH: 40%
- Refrigerant: R290
- Stainless steel interior and exterior with rounded corners for easy cleaning
- Auto defrost
- Three levels of shelving plus base
- Self-closing lockable doors with heavy duty magnetic door seals
- HFCs and CFCs free foam body insulation
- Tropicalised for Australian conditions
- User friendly Digital controls and internal lighting
- Split door design for rapid recovery and energy saving
- Integrated door handle for easy cleaning
- Shelf and shelf support are designed to accommodate 2 x 1/1 GN pan
- Heavy duty evaporator and condenser fans
- Heavy duty castors with front wheel brakes
- 1/2 split door system can lower yearly running cost by up to 30%

2 Years Parts and Labour + 2 Years Parts only Warranty with Product Registration

Your Shipping Specifications

Net Weight (Kg)	117
Width (mm)	680
Depth (mm)	810
Height (mm)	2000
Packing Width (mm)	765
Packing Depth (mm)	855
Packing Height (mm)	2070
Power	240V; 50V; 10A; 465W