





## Tecnodom Blast Chiller & Shock Freezer - DO10

## **Quick Overview**

- Made in Italy
- Built to HACCP specification
- · Digital controller with probe and temperature display
- Time evaporator defrosting
- Ambient operating temp. 43°c
- Tropicalized
- · Ventilated cooling
- Auto defrost
- Self evaporating drainage
- · Internal construction for easy cleaning
- · Self-closing doors
- · Opening the back side and extractable unit for cleaning
- Can be connected to a remote unit
- Stainless steel interior and exterior, except the external base in galvanized steel
- · Rounded internal corners
- Insulation thickness: 40 mm
- Self-closing door with hinges on the left and magnetic gasket
- Chamber probe.
- Core probe.
- · Universal stainless steel pan grids
- Space between grids 70mm
- Internal volume: 190L

## Description

Tecnodom Blast Chiller & Shock Freezer - DO10

Blast chilling and shock freezing are the best natural systems to extend the shelf life of food. Blast Chillers make it possible to lower the temperature at the core of foods that have just been cooked, down to +3 °C in less than 90 min. Reducing bacterial proliferation and dehydration of the food. The final result is preserving the food's quality, color, and fragrance, extending its shelf life. All this enables the chef to work more calmly with a better organization, leaving more time for creativity. They are ideal for commercial business that has a focus on quality, consistency, and time management.

1

- Made in Italy
- Built to HACCP specification
- Digital controller with probe and temperature display
- Time evaporator defrosting
- Ambient operating temp. 43°c
- Tropicalized
- Ventilated cooling
- Auto defrost
- Self evaporating drainage
- Internal construction for easy cleaning
- Self-closing doors
- Opening the back side and extractable unit for cleaning
- Can be connected to a remote unit
- Stainless steel interior and exterior, except the external base in galvanized steel
- · Rounded internal corners
- Insulation thickness: 40 mm
- Self-closing door with hinges on the left and magnetic gasket
- Chamber probe.
- Core probe.
- Universal stainless steel pan grids
- Space between grids 70mm
- Internal volume: 190L

Exterior:  $750 \text{mmW} \times 740 \text{D} \times 1260/1290 \text{H}$ ;  $150 \text{kg Interior: } 610 \text{mmW} \times 410 \text{D} \times 760 \text{H}$  240 V; 1490 W; 10 A outlet required • Chill 25 kg from +70 °C to +3 °C • Deep Freeze 25 kg from +70 °C to -18 °C •  $10 \times 1/1 \text{ GN}$  or  $600 \times 400 \text{ EN}$  pans (40 mm deep)

2 Years Parts and Labour Warranty

## Your Shipping Specifications

Doors	1
Door Type	Hinged Doors
Body	Stainless Steel
Net Weight (Kg)	150
Width (mm)	750
Depth (mm)	740
Height (mm)	1260/1290
Packing Width (mm)	770
Packing Depth (mm)	780
Packing Height (mm)	1390
Power	240V;1490W; 10A outlet required
Warranty	2 Years Parts and Labour