# AMERICAN NRANGE



### **TECHNICAL DATA:**

**Dimensions (W x D x H):** 1524 x 828 x 1200

Total Weight: 370 Kg

Burners: 6 x 26MJ/Hr burners
609mm wide, 16mm thick
32MJ/Hr Raised Griddle plate

**Oven:** 2 x 25MJ/Hr

667 x 572 x 337mm cavity

GAS DETAILS	Natural Gas (NG)	Universal LP Gas (ULPG)
Minimum Supply Pressure	1.13 kPa	2.75 kPa
Operating Pressure	1.0 kPa	2.49 kPa
Total Gas Supply	238MJ/Hr	234MJ/Hr

3/4" BSP connection

NOTE: It is the responsibility of the installing gas plumber to ensure correct supply and connection sustaining appropriate pressure when all appliances are full on

# AAR.6B.24RG

## COMBINATION OVEN RANGE

**PROJECT** 

**ITEM** 

QUANTITY

DATE

The Combination Oven Range Series is designed for heavy duty use and performance. All the latest technology is incorporated to provide the best value for money.

Quality, dependability and customer satisfaction make American Range the ultimate choice.


### **FEATURES & BENEFITS:**


- 303mm open burners / highly polished 16mm thick steel raised griddle plate & salamander over double integrated static oven
- Cast iron trivet is reversible to accept flat pans or woks
- All stainless steel front, sides, rear flue
- Heavy gauge welded frame construction with heavy duty stainless steel landing ledge
- Chrome plated steel legs
- Removable stainless steel door for easy cleaning
- Oven thermostat controls temperature from 70°C 260°C
- Two chrome plated oven racks in enamelled oven bottom, sides, back and door liner
- Two piece, lift-off easy clean open burners
- Removable full width drip pan under burners and grease drawer for griddle
- Open burner Manually lit, No pilot, with flame failure.


  Simple low maintenance
- Raised Griddle burner Piezo ignition with pilot
- Oven burner Piezo ignition with pilot

#### **OPTIONAL EXTRAS:**

- Castor kits
- Additional chrome oven rack







10/13/01. 13/0/2013

