

B+S BLACK SERIES: TF-451S

Split Pan Turbo Fryer

Project: _____ Item: _____




Standard Features:


- AISI 304 Grade Stainless Steel •
- Stainless steel constructed pan with center cool zone 2mm Thick •
- Efficient dual multi-jet target burner •
- +/- 3°C temperature recovery differential •
- Dual over-temperature safety cut-out switches •
- 13.5L oil capacity per section •
- Flame failure fitted as standard •
- Complete with baskets, fish plates and night covers •
- Front access to all components makes service easy
- Pan Dimensions: 415mm L x 150mm W x 80mm H •
 - (Height is measured from the base plate to the oil level mark) 24 Month Warranty


Options:


•

- Natural or LP Gas
- Non-swivel rear castors









MODEL	LENGTH	DEPTH	HEIGHT	GAS CONSUMPTION (Mj/h)	
MODEL	(mm)	(mm)	(mm)	NG	LPG
TF-451S	450	840	1030	76	76

Connections:

GAS (GI)	OIL OUTLET (OO)	SUPPLY PRESSURE (kPa)		
(BSP)	(BSP)	NG	LPG	
³∕₄" (M)	1" (F)	1.0	2.6	

- Combination control valve with inbuilt regulator is supplied within the unit
- Must be installed by an authorised installer in accordance to AS/NZS5601.01

Due to ongoing Product Development, Product Improvement and Research, B+S Commercial Kitchens reserves the right to alter specification without notice.

Approval Number: GMK 10683





