

ITEM#		
MODEL #		
NAME #		
SIS #		
AIA#		



### 218972 (ZCOG101C2U0)

Magistar Combi DI combi boilerless oven with digital control, 10x1/1GN, gas, programmable, automatic cleaning (Australia)

## **Short Form Specification**

#### Item No.

Combi oven with digital interface with guided selection.

- Boilerless steaming function to add and retain moisture.
- AirFlow air distribution system to achieve maximum performance with 5 fan speed levels.
- HP Automatic Cleaning: Automatic and built-in self cleaning system. 5 automatic cycles (soft, medium, strong, extra strong, rinse-only).
- Cooking modes: Programs (a maximum of 100 recipes can be stored); Manual (steam, combi and convection cycles); EcoDelta cooking cycle.
- Automatic backup mode to avoid downtime.
- USB port to download HACCP data, programs and settings. Connectivity ready.
- Single sensor core temperature probe.
- Double-glass door with LED lights.
- Stainless steel construction throughout.
- Supplied with n.1 tray rack 1/1 GN, 67 mm pitch.

#### **Main Features**

- Digital interface with LED backlight buttons with guided selection.
- Boilerless steaming function to add and retain moisture for high quality, consistent cooking results.
- Dry hot convection cycle (max 300 °C) ideal for low humidity cooking. Automatic moistener (11 settings) for boiler-less steam generation.
- EcoDelta cooking: cooking with food probe maintaining preset temperature difference between the core of the food and the cooking chamber.
- Programs mode: a maximum of 100 recipes can be stored in the oven's memory, to recreate the exact same recipe at any time. 4-step cooking programs also available.
- AirFlow air distribution system to achieve maximum performance in chilling/heating evenness and temperature control thanks to a special design of the chamber combined with high precision variable speed fan.
- Fan with 5 speed levels from 300 to 1500 RPM and reverse rotation for optimal evenness. Fan stops in less than 5 seconds when door is opened.
- Single sensor core temperature probe included.
- Automatic fast cool down and pre-heat function.
- HP Automatic Cleaning: Automatic and built-in self cleaning system. 5 automatic cycles (soft, medium, strong, extra strong, rinse-only).
- Grease Collector: predisposed for integrated grease drain and collection for safer operation (dedicated base as optional accessory).
- USB port to download HACCP data, share cooking programs and configurations. USB port also allows to plug-in sous-vide probe (optional accessory).
- Connectivity ready for real time access to connected appliances from remote and HACCP monitoring (requires optional accessory).
- Back-up mode with self-diagnosis is automatically activated if a failure occurs to avoid downtime.
- 2 different chemical options available: solid and liquid (requires optional accessory).
- Capacity: 10 GN 1/1 trays.
- Connectivity ready for real time access to connected appliances from remote and data monitoring (requires optional accessory – contact the Company for more details).
- [NOT TRANSLATED]

### Construction

- Double thermo-glazed door with open frame construction, for cool outside door panel. Swing hinged easy-release inner glass on door for easy cleaning.
- Seamless hygienic internal chamber with all rounded corners for easy cleaning.
- 304 AISI stainless steel construction throughout.
- Front access to control board for easy service.
- IPX 5 spray water protection certification for easy cleaning.
- Supplied with n.1 tray rack 1/1 GN, 67 mm pitch.



-	tional Accessories			•	Hot cupboard base with tray support for 6 & 10 GN 1/1 oven holding GN 1/1 or400x600mm	PNC 922615		1
m	ater softener with cartridge and flow eter (high steam usage)	PNC 920003		•	External connection kit for detergent and	PNC 922618		ì
	ater softener with salt for ovens with attention attention of resin	PNC 921305		•	rinse aid Grease collection kit for GN 1/1-2/1	PNC 922619		1
GI	heel kit for 6 & 10 GN 1/1 and 2/1 N oven base (not for the	PNC 922003			cupboard base (trolley with 2 tanks, open/close device and drain)			
• Pa	sassembled one) air of AISI 304 stainless steel grids,	PNC 922017			on gas 10 GN 1/1 oven	PNC 922623		
• Pa	N 1/1 air of grids for whole chicken (8 per	PNC 922036			Trolley for slide-in rack for 6 & 10 GN 1/1 oven and blast chiller freezer	PNC 922626		
	id - 1,2kg each), GN 1/1 SI 304 stainless steel grid, GN 1/1	PNC 922062		•	Trolley for mobile rack for 6 GN 1/1 on 6 or 10 GN 1/1 ovens	PNC 922630		ı
• Gı	rid for whole chicken (4 per grid - 2kg each), GN 1/2	PNC 922086		•	Stainless steel drain kit for 6 & 10 GN oven, dia=50mm	PNC 922636		Ì
• E>	kternal side spray unit (needs to be ounted outside and includes support	PNC 922171		•	Plastic drain kit for 6 &10 GN oven, dia=50mm	PNC 922637		ĺ
to	be mounted on the oven) aking tray for 5 baguettes in	PNC 922189		•	Grease collection kit for open base (2 tanks, open/close device and drain)	PNC 922639		i
pe	erforated aluminum with silicon pating, 400x600x38mm		_		Wall support for 10 GN 1/1 oven Banquet rack with wheels holding 30	PNC 922645 PNC 922648		
<ul> <li>Ba</li> </ul>	•	PNC 922190			plates for 10 GN 1/1 oven and blast chiller freezer, 65mm pitch	1140 022040	_	•
• Ba	aking tray with 4 edges in aluminum, 00x600x20mm	PNC 922191		•	Banquet rack with wheels holding 23 plates for 10 GN 1/1 oven and blast chiller	PNC 922649		i
• Pa	air of frying baskets	PNC 922239			freezer, 85mm pitch		_	
	SI 304 stainless steel bakery/pastry	PNC 922264			Dehydration tray, GN 1/1, H=20mm	PNC 922651		
•	id 400x600mm	D110 00000F	_		Flat dehydration tray, GN 1/1	PNC 922652		
• Gı	ouble-step door opening kit rid for whole chicken (8 per grid -	PNC 922265 PNC 922266			Open base for 6 & 10 GN 1/1 oven, disassembled	PNC 922653		
• Gı	•	PNC 922321			with 8 racks 400x600mm and 80mm pitch	PNC 922656		
	t universal skewer rack and 4 long	PNC 922324			Heat shield for stacked ovens 6 GN 1/1 on 10 GN 1/1			
	ewers for GN 1/1 ovens niversal skewer rack	PNC 922326			Heat shield for 10 GN 1/1 oven Kit to convert from natural gas to LPG	PNC 922663 PNC 922670		
					——————————————————————————————————————			
	long skewers	PNC 922327			Kit to convert from LPG to natural gas	PNC 922671		
	ultipurpose hook	PNC 922348			Flue condenser for gas oven	PNC 922678		
10	flanged feet for 6 & 10 GN, 2", 00-130mm	PNC 922351			Fixed tray rack for 10 GN 1/1 and 400x600mm grids	PNC 922685		
	rid for whole duck (8 per grid - 1,8kg ach), GN 1/1	PNC 922362			Kit to fix oven to the wall	PNC 922687		
• Th	nermal cover for 10 GN 1/1 oven and ast chiller freezer	PNC 922364			4 high adjustable feet for 6 & 10 GN ovens, 100-115MM	PNC 922688		
• Tr	ay support for 6 & 10 GN 1/1 sassembled open base	PNC 922382			Tray support for 6 & 10 GN 1/1 open base Reinforced tray rack with wheels, lowest	PNC 922694		
	all mounted detergent tank holder	PNC 922386			support dedicated to a grease collection tray for 10 GN 1/1 oven, 64mm pitch			
• US	SB SINGLE POINT PROBE	PNC 922390		•	Detergent tank holder for open base	PNC 922699		1
• Tr	ay rack with wheels 10 GN 1/1, 5mm pitch (std)	PNC 922601			Bakery/pastry runners 400x600mm for 6 & 10 GN 1/1 oven base	PNC 922702		ì
• Tr	ay rack with wheels, 8 GN 1/1,	PNC 922602			Wheels for stacked ovens	PNC 922704		
	akery/pastry tray rack with wheels	PNC 922608		•	Spit for lamb or suckling pig (up to 12kg) for GN 1/1 ovens	PNC 922709		ı
40	00x600mm for 10 GN 1/1 oven and		_	•	Mesh grilling grid	PNC 922713		1
	ast chiller freezer, 80mm pitch (8				Probe holder for liquids	PNC 922714		1
• SI	nners) ide-in rack with handle for 6 & 10 GN	PNC 922610			Exhaust hood with fan for 6 & 10 GN 1/1 ovens	PNC 922728		
• O	1 oven pen base with tray support for 6 & 10	PNC 922612		•	Exhaust hood without fan for 6&10 1/1GN ovens	PNC 922733		ì
	N 1/1 oven upboard base with tray support for 6	PNC 922614		•	Fixed tray rack, 8 GN 1/1, 85mm pitch	PNC 922741		ì
	10 GN 1/1 oven		_	•	Fixed tray rack, 8 GN 2/1, 85mm pitch	PNC 922742		i













4 high adjustable feet for 6 & 10 GN ovens, 230-290mm	PNC 922745	
Tray for traditional static cooking, H=100mm	PNC 922746	
Double-face griddle, one side ribbed and one side smooth, 400x600mm	PNC 922747	
TROLLEY FOR GREASE     COLLECTION KIT	PNC 922752	
Water inlet pressure reducer	PNC 922773	
Non-stick universal pan, GN 1/1, H=20mm	PNC 925000	
<ul> <li>Non-stick universal pan, GN 1/1, H=40mm</li> </ul>	PNC 925001	
<ul> <li>Non-stick universal pan, GN 1/1, H=60mm</li> </ul>	PNC 925002	
<ul> <li>Double-face griddle, one side ribbed and one side smooth, GN 1/1</li> </ul>	PNC 925003	
Aluminum grill, GN 1/1	PNC 925004	
<ul> <li>Frying pan for 8 eggs, pancakes, hamburgers, GN 1/1</li> </ul>	PNC 925005	
• Flat baking tray with 2 edges, GN 1/1	PNC 925006	
<ul> <li>Baking tray for 4 baguettes, GN 1/1</li> </ul>	PNC 925007	
<ul> <li>Potato baker for 28 potatoes, GN 1/1</li> </ul>	PNC 925008	
<ul> <li>Non-stick universal pan, GN 1/2, H=20mm</li> </ul>	PNC 925009	
<ul> <li>Non-stick universal pan, GN 1/2, H=40mm</li> </ul>	PNC 925010	
<ul> <li>Non-stick universal pan, GN 1/2, H=60mm</li> </ul>	PNC 925011	
<ul> <li>Compatibility kit for installation on previous base GN 1/1</li> </ul>	PNC 930217	













#### **Electric**

Supply voltage:

218972 (ZCOG101C2U0) 230-240 V/1 ph/50 Hz

Electrical power, default: 1.1 kW Electrical power max.: 1.1 kW

Circuit breaker required

**Gas Power:** 22.8 kW Standard gas delivery: Natural Gas G20

ISO 7/1 gas connection diameter:

1/2" MNPT

**Total thermal load:** 77725.2 BTU (22.8 kW)

Water:

Water inlet "FCW"

3/4" connection: 1-6 bar Pressure, bar min/max: Drain "D": 50mm

Max inlet water supply

temperature: 30 °C **Chlorides:** <10 ppm **Conductivity:** >50 µS/cm

Electrolux Professional recommends the use of treated water, based on testing of specific water conditions.

Please refer to user manual for detailed water quality information.

**Installation:** 

Clearance: 5 cm rear and right

hand sides.

867 mm

Suggested clearance for

service access: 50 cm left hand side.

Capacity:

Clearance:

10 - 1/1 Gastronorm

Max load capacity: 50 kg

**Key Information:** 

**Door hinges:** 

External dimensions,

Width:

External dimensions,

Depth:

775 mm

External dimensions,

**Height:** 1058 mm Net weight: 139 kg Shipping weight: 157 kg Shipping volume: 1.06 m<sup>3</sup>









