# **0S0PE4**



## TWO PLATE ELECTRIC BOILING TABLE

Electric boiling range with AISI 304 stainless steel structure, 20/10 mm thickness top. Cooking square plates made of cast iron, watertight, fitted with thermal protection devices, 7-position switch for each plate.







| Power supply      | Electricity | Product fitting up | Counter Top |
|-------------------|-------------|--------------------|-------------|
| Worktop thickness | 2 mm        |                    |             |

#### **Functional features**

- · Nr. 2 cast iron square electric cooking plates, diamensions each plate 22.7 x 22.7 cm.
- · Heating power of each plate: 2.6 kW, controlled by 7-position switch.
- Pre-set appliance for installation on under compartment, support surface; with specific accessories on bridge solution and cantilever on beam.

#### **Constructional features**

- · Work top made in AISI 304 stainless steel, 20/10 thickness with Scotch Brite finish.
- Control panel made in AISI 304 stainless steel, thickness 12/10 mm, Scotch-Brite finish. Side paneling made in AISI 304 stainless steel, back panel in stainless steel.
- · Side-by-side top juxtaposition very rigid and accurate guaranteeing max quality and hygiene.
- · Worktop with pressed recess for collection of juices and for cooking plate housing.
- · Insulation to reduce surface temperatures on the front of the cooking top and to improve user comfort.
- · Metal ergonomic knobs with rubber protection against water infiltration.
- Radiused rear splashback on the worktop h = 4 cm, with built-in chimney for heat exhaust, removable enamelled cast iron guard.
- Non-slip rubber feet h = 2 cm.
- · Access to all components through front compartment or control console.

### Safety equipment and approvals

- · Safety thermostat, integrated to the plates, against overheating due to idling.
- · CE approvals in respect of all directives and regulations.
- Approval to European Standard EN 1672-2 Hygienic Design.
- · IPX4 protection rating.

### **Optional**

Water filling tap.

#### **Technical Data**

| Working voltage | 400V 3N ~ 50 ÷60 Hz | Electric Power | 5,2 kW      |
|-----------------|---------------------|----------------|-------------|
| Dimensions      | 40x72x25 cm         | Packing        | 46x82x65 cm |