

ELECTRIC GRIDDLE SMOOTH CHROMIUM PLATE

Griddle made of AISI 304 stainless steel, 20/10 mm thickness top. Cooking plate made in Fe510D steel with hard chromium surface treatment. EVEN-PRO SYSTEM. Delivered with: plate plug. Heating by two independent heating elements made in AISI 309 stainless steel placed under the plate, safety thermostat. Working temperature (min-max): 70-260°C.







Plate	Cr - smooth	Power supply	Electricity
Product fitting up	Counter Top	Worktop thickness	2 mm

Functional features

- · Smooth cooking plate made in special Fe510D steel with hard chromium surface treatment, thickness 12 mm.
- · Plate with mirror finish, recessed into the worktop; welded around the perimeter and sealed.
- · Operating temperature: 70-260°C.
- · Dimensions of the cooking plate (W x D): 730 x 530 mm. Frontal simmering zone 50 mm.
- · n. 2 independent cooking areas power rated at 5.1 kW each
- EVEN-PRO Ensures high cooking uniformity and temperature stability. The cooking heating elements are integrated with a 5 mm aluminum diffuser ensuring quick temperature rise, high efficiency in the heat transfer, temperature stability and energy efficiency.
- EASY-WASH: this is the program to clean the cooking plate bringing the surface temperature up to 75°C, in order to wash it reducing water and detergent.
- · Commutable to 230V3 50/60 Hz
- · Two groups of three + three armoured heating elements made of in AISI 309 stainless steel, each heating a half plate.
- Pre-set appliance for installation on under compartment, support surface; with specific accessories on bridge solution and cantilever on beam.

Constructional features

- · Work top made in AISI 304 stainless steel, 20/10 thickness with Scotch Brite finish.
- Control panel made in AISI 304 stainless steel, thickness 12/10 mm, Scotch-Brite finish. Side paneling made in AISI 304 stainless steel, back panel in stainless steel.
- · Side-by-side top juxtaposition very rigid and accurate guaranteeing max quality and hygiene.
- Fett drain outlet diameter 32 mm with removable heat-resistant food-grade plastic plug.
- · Cooking fat drainage eased by the sloping plate and collection in the pull-out drawer capacity 1.5 lt.
- · Metal ergonomic knobs with rubber protection against water infiltration.
- Radiused rear splashback on the worktop h = 4 cm, with built-in chimney for heat exhaust, removable enamelled cast iron guard.
- · Non-slip rubber feet h = 2 cm.
- · Access to all components through front compartment or control console.

Safety equipment and approvals

- · Safety thermostat protecting the appliance and electric parts.
- · Max temperature safety thermostat.
- · CE approvals in respect of all directives and regulations.
- Approval to European Standard EN 1672-2 Hygienic Design.
- The product conforms to EC 1935/2004 Regulation and 21/03/1973 Rulemaking (Materials and Objects that are destined to come into Contact with Aliments).
- · IPX4 protection rating.

Optiona

· Splash guards, cleaning plate scraper and blades; pipe for the water discharge during the cleaning of the plate.

Technical Data

Working voltage 400V 3N~ / 230V 3~ / 50÷60 Hz Electric Power 10,2 kW



1S0FT4E



Dimensions 80x72x25 cm Packing 86x82x65 cm