
1S0VTR



INFRARED PYROCERAM COOKING RANGE 4 AREAS









| Power supply | Electricity | Product fitting up | Counter Top |
|-------------------|-------------|--------------------|-------------|
| Worktop thickness | 2 mm | | |

Functional features

- · Cooking surface in pyroceram, flush with worktop and sealed.
- · n. 4 independent cooking areas power rated at 2.5 kW each
- · Power regulator, 10 levels.
- · Electronic diagnostic system with signaling alarm code through light on the controle console.
- · Indirect cooking.
- · Heating by incandescent heating elements.
- · Easy to clean thanks to a smooth, hermetic glass ceramic surface.
- · Commutable to 230V 3F 50/60 Hz
- Pre-set appliance for installation on under compartment, support surface; with specific accessories on bridge solution and cantilever on beam.

Constructional features

- · Work top made in AISI 304 stainless steel, 20/10 thickness with Scotch Brite finish.
- Control panel made in AISI 304 stainless steel, thickness 12/10 mm, Scotch-Brite finish. Side paneling made in AISI 304 stainless steel, back panel in stainless steel.
- · Side-by-side top juxtaposition very rigid and accurate guaranteeing max quality and hygiene.
- · Pyroceram glass, thickness 6 mm, max load weight: 0.2 kg/cm².
- · Two glass surfaces with dimension each: 32 x 56 cm.
- · Metal ergonomic knobs with rubber protection against water infiltration.
- Radiused rear splashback on the worktop h = 4 cm, with built-in chimney for heat exhaust, removable enamelled cast iron guard.
- Non-slip rubber feet h = 2 cm.
- · Access to all components through front compartment or control console.

Safety equipment and approvals

- · Thermal protection for over temperature.
- · Residual heat indicator light under glass.
- · CE approvals in respect of all directives and regulations.
- · Approval to European Standard EN 1672-2 Hygienic Design.
- · IPX4 protection rating.

| T | е | C | hi | ni | C | a | П |) | a | ta | a |
|---|---|---|----|----|---|---|---|---|---|----|---|
| | | | | | | | | | | | |

| | Working voltage | 400V 3N~ / 230V 3~ / 50÷60 Hz | Net Weight | 38 kg |
|--|-----------------|-------------------------------|----------------|-------------|
| | Gross Weight | 45 kg | Electric Power | 10 kW |
| | Dimensions | 80x72x25 cm | Packing | 86x82x65 cm |

