

4 ELECTRIC PLATES RANGE ON ELECTRIC STATIC OVEN - 230V

Electric boiling range with AISI 304 stainless steel structure, 20/10 mm thickness top. Cooking square plates made of cast iron, watertight, fitted with thermal protection devices, 7-position switch for each plate. Electric static oven in AISI 430 stainless steel with thermostat, removable stainless steel guides useful for GN 2/1 containers.







Oven Type	Electric static oven GN 2/1	Power supply	Electricity
Product fitting up	with integrated undercompartment	Worktop thickness	2 mm

Functional features

- · Nr. 4 cast iron square electric cooking plates, diamensions each plate 22.7 x 22.7 cm.
- · Heating power of each plate: 2.6 kW, controlled by 7-position switch.
- · Electric static oven rated at 7,2 kW
- · Oven capacity: GN 2/1 (or GN 1/1) containers, on demountable stainless steel tray rack with three height levels.
- Cooking oven temperature control from 100°C to 300°C. Three modes of operation: lower heating element, upper heating element, lower and upper heating elements simultaneously.
- · Pre-set appliance for installation freestanding on feet.

Constructional features

- · Work top made in AISI 304 stainless steel, 20/10 thickness with Scotch Brite finish.
- Control panel made in AISI 304 stainless steel, thickness 12/10 mm, Scotch-Brite finish. Side paneling made in AISI 304 stainless steel, back panel in stainless steel.
- Side-by-side top juxtaposition very rigid and accurate guaranteeing max quality and hygiene.
- · Worktop with pressed recess for collection of juices and for cooking plate housing.
- · Insulation to reduce surface temperatures on the front of the cooking top and to improve user comfort.
- Oven cooking chamber made of AISI 430 stainless steel thickness 10/10, glossy finish. Dimensions (W x D x H) 53 x 65 x 31 cm. Insulation by high density ceramic fiber panel. Oven double-walled door made of satin finished AISI 304 stainless steel, inner door made of AISI 441 stainless steel, insulated by high density glass wool. Full width chrome aluminum handle. Heavy Duty hinges. Silicone rubber gasket on the oven front to ensure perfect closure.
- · Enamelled steel oven demountable bottom.
- · Metal ergonomic knobs with rubber protection against water infiltration.
- Radiused rear splashback on the worktop h = 4 cm, with built-in chimney for heat exhaust, removable enamelled cast iron quard.
- Height adjustable floor-mounted feet in AISI 304 stainless steel, non-scratch sole in insulating plastic material. Feet are supplied at a fixed height of 15 cm. Foot extension 5 cm (minimum height / maximum height: 87.5 / 92.5 cm).
- · Maintenance of inner components does not require appliance displacement.
- · Access to all components through front compartment or control console.

Safety equipment and approvals

- · Safety thermostat, integrated to the plates, against overheating due to idling.
- Safety thermostat against oven overheating.
- · CE approvals in respect of all directives and regulations.
- Approval to European Standard EN 1672-2 Hygienic Design.
- · IPX4 protection rating.

Standard equipment

· The oven is delivered with 1 chromium plated grid GN 2/1.

Optional

· Water filling tap, wheels.

Technical Data



4 E

1S1PE2E



Working voltage 230V 3 ~ 50 ÷ 60 Hz Electric Power 18,3 kW

Dimensions 80x72x90 cm Packing 86x82x130 cm