





Stainless Steel Double Door Workbench Freezer - TL1500BT

Quick Overview

- Freezer -18 to -22°C
- Solid Door freezer Ambient 38°C
- Fan-forced evaporator cooling
- Auto defrost
- Self-evaporating drainage
- Insulation is CFC & HCFC free
- · Heated door frame on freezers
- · Internal corners constructed for easy cleaning
- 100mm wall clearance required for ventilation
- Castors

Description

700 Series

Stainless steel double solid door freezer FREEZER • -18 to -22 ° C

S/S Double Door - 345 Litre

Features:

- Freezer -18 to -22°C
- Solid Door freezer Ambient 38°C
- Fan-forced evaporator cooling
- Auto defrost
- Self-evaporating drainage
- Insulation is CFC & HCFC free
- · Heated door frame on freezers
- Internal corners constructed for easy cleaning
- 100mm wall clearance required for ventilation
- Castors

1

| Dimension: 1500mmW × 700D × 865H; |
|--|
| Ambient / RH%: 38/50 |
| Power: 240V; 530W; 10A outlet required |
| |
| 2 Years Parts and Labour + 2 Years Parts only Warranty with Product Registration |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |

Your Shipping Specifications

| Net Weight (Kg) | 105 |
|---------------------|---|
| Width (mm) | 1500 |
| Depth (mm) | 700 |
| Height (mm) | 850 |
| Packing Width (mm) | 730 |
| Packing Depth (mm) | 1540 |
| Packing Height (mm) | 900 |
| Power | 240V; 530W; 10A Outlet Required |
| Warranty | 2 Years Parts and Labour + 2 Years Parts Only for Products Registered within 14 Days of Invoice |