

Brullen i26 PRO Twin System

Two Flavour plus Twist | Countertop Machine | Pasteurize Option | Air Pump Option



Product Details

Colors

Comes with standard color of Black or Silver. Visit the ORAFOL website for more colour inspiration! <https://bit.ly/3AJ5B8Y>

Power Voltage

220-240V / 50-60Hz // 200V
3 phase or 110V 60Hz (US / CAN)

Countertop Machine

Two Flavour plus Twist

Machine Size

W555 x D750 x H960
(mm)

Overrun

15 - 45% (Overrun - Gravity Feed), 30 - 80% (Overrun - Air Pump)

Serves

Approx. 450 - 700 serves per hour depending on product (*80 gram serves)

Machine Weight

Gravity Feed 165kg / Air Pump 180kg

Output

3.60 kW

Product Specification

Refrigeration System

Twin Twist System (2x compressors)

Overrun - Gravity Feed

15 - 45%

Overrun - Air Pump

30 - 80%

Mix Hopper Capacity

2 x 12 L

Mix Hopper Agitator

Yes

Scraper Blade

Plastic

Freezing Cylinder Capacity

2 x 2L

Compressor

Tecumseh 1.75 HP x 2

Mix Hopper Cooling

Yes

Refrigerant Type

R404a

Pasteurize

Optional

Defrost

Optional

Condenser

Air

Dryer

Danfoss

Expansion Valve

Danfoss

Warm Air Dispensed

Rear

Ventilation required

Refer to equipment manual

Operator Menu

Soft Touch Buttons

Electrical Phase

Single

Nominal Power

3.6 kW

Power Outlet/Plug

20 AMP single phase dedicated circuit

Machine Weight

Gravity Feed 165kg / Air Pump 180kg

Machine Size W x D x H

W555 x D750 x H960 (mm)

Packaging Size W x D x H

W600 x D950 x H1100 (mm)

Wash Kit / Hose (Requires Plumbing)

Optional

Electrical Specifications Volt/Hz

220-240V / 50-60Hz // 200V 3 phase or 110V 60Hz (US / CAN)

Cups per Hour

Approx. 450 - 700 serves per hour depending on product (*80 gram serves)

Machine Weight with Packaging

Gravity Feed 190kg / Air Pump 210kg

Motor and Gearbox

Transtecno

*Transtecno motor and gearbox available for Brullen machines from September 2024 production onwards.

