



Bonvue Dual-Access Refrigerated Deli, Meat and Seafood Display Case - AMS-15DD

Quick Overview

- Gross Volume: 993L
- Max Ambient Temperature: 30°C, 55%RH
- Temperature Range: -1 to +5 ° C
- Efficient Freshness: Double gravity coil for even cooling, perfect for deli, meat and seafood products
- Durable Slanted Front Glass: Double-layer tempered for clear, safe display
- Adjustable Shelves: Easily modify for different heights
- LED Lighting: Showcases items with individually wired shelf lights
- Insulated Sliding Rear Doors: Easy staff access while retaining cold air
- Extra Refrigerated Storage: Spacious rear area for stock
- Optimised Cooling: Over-sized components and slow fans maintain freshness
- Auto Defrost: Timer system prevents ice build-up
- No Plumbing Needed: Self-contained for hassle-free installation
- Stainless Steel Interior: Floor and grille designed for durability and airflow

Description

Bonvue Dual-Access Refrigerated Deli, Meat and Seafood Display Case - AMS-15DD

The dual-access design allows staff to restock from the rear without interrupting customers at the front, making it ideal for high-traffic retail settings like butcher shops, seafood counters, and deli displays. It streamlines service flow and keeps the presentation neat and professional throughout busy trading hours.

Key Features

- Gross Volume: 993L
- Max Ambient Temperature: 30 °C, 55%RH
- Temperature Range: -1 to +5 °C
- Efficient Freshness: Double gravity coil for even cooling, perfect for deli, meat and seafood products
- Durable Slanted Front Glass: Double-layer tempered for clear, safe display
- Adjustable Shelves: Easily modify for different heights
- LED Lighting: Showcases items with individually wired shelf lights
- Insulated Sliding Rear Doors: Easy staff access while retaining cold air
- Extra Refrigerated Storage: Spacious rear area for stock
- Optimised Cooling: Over-sized components and slow fans maintain freshness
- Auto Defrost: Timer system prevents ice build-up
- No Plumbing Needed: Self-contained for hassle-free installation
- Stainless Steel Interior: Floor and grille designed for durability and airflow

1 Year Parts & Labour Plus 1 Year Parts Only Warranty When Products Registered Within 14D Of Invoice.

Your Shipping Specifications

Product Condition	New
Doors	2
Door Type	Sliding Doors
Body	Stainless Steel
Gross Volume	993L
Max Ambient Temperature	30 , 55%RH
Temperature Range	-1 to +5 ° C
Form Factor	Display
Net Weight (Kg)	174
Width (mm)	1523
Depth (mm)	855
Height (mm)	1406
Packing Width (mm)	1585
Packing Depth (mm)	915
Packing Height (mm)	1560
Power	240V, 650W/10A
Warranty	1 Year Parts & Labour Plus 1 Year Parts Only Warranty When Products Registered Within 14D Of Invoice.